



Steam Sterilizer Autoclave

DESCRIPTION :

- The temperature gauge indicates both the inside temperature and the sterilize pressure.
- The gauge is graduated in two-degree increments
- Easy operation with cycle timer setting at standard 127 °C
- Environmental stainless steel materials of boiler chamber surface.
- Large chamber volume up to 16.2 Liters allows for efficient sterilize process.
- The safety thermostat control automatically turns off to protect the unit from overheat.
- Double pressure adjustments can adjust to optimal inter pressure and self vent if over the standard pressure.
- Self-complete program The audible tone sounds and when sterilization is complete and .
- Back drain valve design allows for easy cleaning and maintenance.
- Stainless and durable sterilize box ensure the sterilize operation.
- Metal instruments and gauze require the same sterilize time.

CONTENTS:

Chamber Capacity 23cm x 39cm (depth)

Interior Capacity 16.20(L)

Exterior Size 47cm x 33cm x 41cm

Sterilize Temperature Highest 127°C, including under temperature

Sterilize Pressure Highest 1.5kg/cm², including under pressure

Sterilize Time 30 minutes

Heater 1,000W

Material Quality Stainless steel SUS#304. Boiler chamber with burnished surface.

Electric Current 220V/7A

Safety Features Double pressure adjustment: adjusts interior pressure if over standard value with automatic vent.